

Concept: Low-glare architectural LED wall pack for commercial and industrial outdoor lighting — retail centers, schools, restaurants, and factories. Die-cast aluminum housing with a low-glare lens for visual comfort.

Lamp Type: Integral LED, 120–277V, field-selectable 15/30/50/72W and 3000/4000/5000K, up to 8,407 lumens, 70CRI, Forward Throw (Type I).

Dimensions: L: 18.1" · W: 9.05" · H: 9.05"

Finish: Bronze powder coat.

Certification: cULus for Wet Locations, DLC 5.1.



Key Features

- Field-selectable wattage (15/30/50/72W)
- Field-selectable CCT (3000/4000/5000K)
- Low-glare lens for visual comfort
- Die-cast aluminum housing
- Quick-mount plate for easy installation
- Wet location rated, DLC 5.1

Ordering Guide

A. SERIES	B. LAMP TYPE	C. FINISH

A. SERIES

CODE	NAME
AWQS	Low-Glare Architectural Wall Pack

C. FINISH

CODE	NAME
BZ	Bronze

B. LAMP TYPE

CODE	NAME
72W	15/30/50/72W & 3000/4000/5000K — field-adjustable

Field-adjustable: Wattage (15/30/50/72W) and CCT (3000/4000/5000K) are set at the fixture — not selected in the part number.

Voltage: 120–277V universal (standard).

Example part number: AWQS-72W-BZ