

# P1 BOLLARD

## OUTDOOR COMMERCIAL

Project Name: \_\_\_\_\_ Prepared by: \_\_\_\_\_

Approved by: \_\_\_\_\_ Comments: \_\_\_\_\_

P1	-	-	-	-
<b>Series</b>		<b>Design</b>	<b>Lamp Type</b>	<b>Reflector</b>
	/			
<b>Finish</b>	<b>Accessories</b>			



Glass

Louver

Cone

Round Dome  
RD = Round Dome

### Series

**P1 - Round Dome, Round Flat, Square Flat**

**P1-RD:** Dia: 7in, Height: 42 1/4in

**P1-RF:** Dia: 7in, Height: 41 3/8in

**P1-SF:** Length: 7in, Height: 41 3/8in

**Application:** Pathways, Parking Lots, Plazas, Entrance Ways, Parks and Landscape Accents.

**Material:** Extruded Aluminum Housing, Powder Coat Finish, Clear Polycarbonate Lens.

**Mounting:** Cast Aluminum Plate. 3 Anchor Bolts

**Driver:** 120-277V, 50/60Hz, 0-10V Dimming down to 10%.

**Listing:** CSA: Listed for Wet Locations, ANSI/UL 1598, 8750 IP65 Sealed LED Compartment.



Glass

Louver

Cone

Round Flat  
RF = Round Flat

### Design

**RD:** Round Dome, **RF:** Round Flat, **SF:** Square Flat

### Lamp Type

**LED: Light Emitting Diode**

**LED15W-30K:** LED22W, 120-277V, 3000K (70W HID Equivalent), Electronic Driver

**LED15W-40K:** LED22W, 120-277V, 4000K (70W HID Equivalent), Electronic Driver

**LED15W-50K:** LED22W, 120-277V, 5000K (70W HID Equivalent), Electronic Driver

**Turtle LED: Turtle Friendly Light**

**TLM15W:** 585nm Wavelength, 120-277V, 15W, (70W HID Equivalent), Electronic Driver

**CF: Compact Fluorescent**

**CF142:** 1x42W, 120-277V, Electronic Ballast

**CF157:** 1x57W, 120-277V, Electronic Ballast



Glass

Louver

Cone

Square Flat  
SF = Square Flat

### Reflector

**PRC:** Parabolic Cone, **LVR:** Louver, **BG3:** Borosilicate Glass, Type 3, **BG5:** Borosilicate Glass, Type 5

### Finish

**BK:** Black, **BZ:** Bronze

### Accessories

**BULED-SM:** 90 Min. Small LED Battery Backup, 120-277V/50-60Hz

# BockLighting

**P:** (216) 912-7050  
**E:** Sales@bocklighting.com  
**www.BockLighting.com**

