

# LED by Bock Lighting

Cree's LMH2

## RLM Series

### Features

- Industry-leading light-source efficacy of 97 lm/W (steady state)
- Cree TrueWhite® Technology, >90 CRI
- Kelvin: 27, 35, 40K
- Power input: 120 - 277V
- Driver options: Osram OT25W (UNV & 0-10V) or ERP EBR15 (120V & 0-10V)
- Supports 0-10V dimming down to 10%
- 5 year system warranty
- Designed to last 50,000
- No UV in light output
- No mercury in light source
- Upgradeable / Replaceable
- Fixture manufactured to UL Standards I598 & 8750.



LMH2 with Dome Lens

Module	Lumens	Wattage	Cree Part	Driver	Voltage	Dimming
LED850	850	8.95W	LMH020-0850	EBR15 or OT25W	120V or UNV	TRIAC or 0-10V
LED1250	1250	13.16W	LMH020-1250	EBR15 or OT25W	120V or UNV	TRIAC or 0-10V

### Compatible Reflectors:

Standard Dome:	512, 514, 516, 518, 520	Radial Wave:	RW16, RW20
Step Neck Dome:	SN512, SN514, SN516, SN518, SN520, SN524 SN512GV, SN514GV, SN516GV, SN518GV	Downlight Reflector:	RW16GV, RW20GV 914DL, 916DL, 918DL, 924DL 918DLGV
Shallow Dome:	412, 414, 416	Uplight Reflector:	918UL 918ULGV
Step Neck Deep Bowl:	SN908, SN910, SN912 SN908GV, SN910GV, SN912GV	Self Ballasted Dome:	516B, 520B
Step Neck Angle:	SN608, SN610, SN612, SN614 SN608GV, SN610GV, SN612GV, SN614GV	Self Ballasted Cone:	110B, 116B, 120B
Emblem Sign:	6208, 6210, 6212, 6214, 6218, 6222	Self Ballasted Deep Bowl:	918B