

GLP1

Canopy Lighting



A

SERIES

B

LAMP TYPE

C

ACCESSORIES

A SERIES

Application: Schools, Parking Garages, Office Complexes and any area prone to vandalism.
Material: Die Cast Aluminum Housing, Powder Coated Architectural Bronze, Polycarbonate Opal Lens

Dimensions:

GLP1M: L: 9in, W: 9in, H: 4in

GLP1L: L: 12.5in, W: 12.5in, H: 4.25in

Mounting: Mount Directly Over a 4in Recessed Outlet Box

Lamp Type: LED - Array - 27/54W, 120-277V or 347-480V, 0-10V Dimming down to 10%, Type V Optics

Listing: CSA Listed for Wet Locations, IP65 Sealed LED Compartment

GLP1M - GLP1 Medium Wall Mounted

GLP1L - GLP1 Large Wall Mounted

B LAMP TYPE

LED27W-40K-(UNV/347) - LED27W Array, 2700lm, 40K, 120-277V or 347-480V, 0-10V Dimming down to 10%, 100W HID Equivalent *GLP1M only

LED27W-50K-(UNV/347) - LED27W Array, 2800lm, 50K, 120-277V or 347-480V, 0-10V Dimming down to 10%, 100W HID Equivalent *GLP1M only

LED54W-40K-(UNV/347) - LED54W Array, 5400lm, 40K, 120-277V or 347-480V, 0-10V Dimming down to 10%, 175W HID Equivalent *GLP1L only

LED54W-50K-(UNV/347) - LED54W Array, 5700lm, 50K, 120-277V or 347-480V, 0-10V Dimming down to 10%, 175W HID Equivalent *GLP1L only

C ACCESSORIES

PC1 - Photocell, 120VAC

PC3 - Photocell, 120-277VAC

MS - Microwave Sensor with Dimming for Mounting Heights of 8 to 40' (127-277V Only)

BA - Batter Backup, 90 Minutes