

AT STYLE REFLECTOR

Decorative Reflectors



A DESIGN

Concept: AT Style - Trapezoid Aluminum Reflector
Lamp Type: INC, LED Available.
Mounting: Cord Mounted
Finish: Powder Coating
Certification: cULus for Damp Locations

- AT08** 8in AT Style Reflector **AT12** 12in AT Style Reflector **AT16** 16in AT Style Reflector **AT20** 20in AT Style Reflector
- AT24** 24in AT Style Reflector

AT STYLE REFLECTOR

Decorative Reflectors

B FINISH

Powder Coat Finishes

 GXX To be determined.	 G0 Black	 G1 White	 G2 Red	 G3 Yellow	 G4 Blue	 G5 Green	 G6 Brown	 G7 Verdigris
 G8 Dark Bronze	 G9 Silver	 G10 Dark Green	 G11 Copper	 G12 Brushed Aluminum	 G13 Tan	 G14 Gunmetal	 G15 Rust	 G16 Silver Wrinkle
 G17 Architectural Bronze	 G18 Rock Garden Green	 G20 Silver Cast	 G21 Hammered Copper	 G22 Dark Platinum	 G23 Silver Camera	 G24 Orange	 G25 Navy Blue	 G26 Chrome
 G27 Matte Black	 G28 Sun Gold	 G29 Brilliant Blue	 G30 Mirror Black	 G50 Neon Orange	 G51 Neon Pink	 G52 Neon Yellow	 G53 Lime Green Neon	

AT STYLE REFLECTOR

Decorative Reflectors

C LAMP TYPE

Lamp Type

Concept: LAC02 is a versatile LED module that can be installed inside most of Bock's RLMs. It gives the flexibility in lumens and kelvin on the jobsite.

LED: Adjustable Kelvin LEDs with 3 x Lumens & 4 x Kelvins

Lumens: 1500, 1850, or 2400LM

Kelvin: 3000, 3500, 4000, or 5000K

CRI: 80

Jelly Jar: 41 Compatible with Wire or Cast Guard

Guard: Compatible with 31DCG Cast Guard and 31 Wireguard

Dimming: 0-10V Down to 10%

Voltage: 120-277V 50/60Hz

Color: White

Certification: cULus



LAC02 LAC Integral LEDs with Adjustable Lumens & Kelvin, 26W

LBAC1-1 - Indoor Only

LED: 1 x Cree CMA25, Available with either 27/30/35/40K Driver: ERP PSB Series, 120/277V, 0-10V Dimming



LBAC1-1-1600-XXK LBAC1 - Single Module, 1600LM, 15W

LBAC1-1-1800-XXK LBAC1 - Single Module, 1800LM, 17W

LBAC1-1-2000-XXK LBAC1 - Single Module, 2000LM, 18W

LBAC1-1-2500-XXK LBAC1 - Single Module, 2500LM, 23W

LBAC1-1-3000-XXK LBAC1 - Single Module, 3000LM, 27W

LBAC1-1-4000-XXK LBAC1 - Single Module, 4000LM, 36W

LBAC1-1-5000-XXK LBAC1 - Single Module, 5000LM, 45W

AT STYLE REFLECTOR

Decorative Reflectors

LVFV1

LED: Bridgelux Vero. Available with either 27/30/35/40K Driver: ERP PSB Series, 120/277V, 0-10V Dimming



LVFV1-1250-XXK LVFV1 -
1250LM, 10W, Indoor

LVFV1-1500-XXK LVFV1 -
1500LM, 12W, Indoor

LVFV1-1700-XXK LVFV1 -
1700LM, 14W, Indoor

LVFV1-2000-XXK LVFV1 -
2000LM, 16W, Indoor

LVGV1

LED: Bridgelux Vero18SE

Driver: AC Electronics - AC15CD350AT2S, 120-277V, 0-10V Dimming

LVGV1-1250-XXK LVGV1 -
1250LM

LVGV1-1500-XXK LVGV1 -
1500LM

LVGV1-1700-XXK LVGV1 -
1700LM


LVGV1-2000-XXK LVGV1 -
2000LM

AT STYLE REFLECTOR

Decorative Reflectors

D LENS

41 Glass Jelly Jar



41 41 - Clear



41CAM 41 Amber



41CBL 41 Blue



41CGN 41 Green



41COP 41 Opal



41CRD 41 Red



41F 41 Frost



41PR 41 Prismatic




41S 41S - Clear Short



41SF 41SF - Frost Short

41SPR 41 Short - Prismatic

41 Lexan



41L 41 Lexan Clear



41LCAM 41 Lexan Amber



41LCBL 41 Lexan Blue



41LCGN 41 Lexan Green



41LCOP 41 Lexan Opal



41LCRD 41 Lexan Red



41LPR 41 Lexan Prismatic

AT STYLE REFLECTOR

Decorative Reflectors

42 Glass Jelly Jar



42 42 Clear

Max: INC - 300W, HID - 175W, CFL - 42W



42CAM 42 Amber

Max: INC - 200W, HID - 175W, CFL - 42W



42CBL 42 Blue

Max: INC - 200W, HID - 175W, CFL - 42W



42CGN 42 Green

Max: INC - 200W, HID - 175W, CFL - 42W



42COP 42 Opal

Max: INC - 200W, HID - 175W, CFL - 42W



42CRD 42 Red

Max: INC - 200W, HID - 175W, CFL - 42W



42PR 42 Prismatic

Max: INC - 300W, HID - 175W, CFL - 42W

AT STYLE REFLECTOR

Decorative Reflectors

42 Lexan



42L 42 Lexan Clear



42L-CAM 42 Lexan Amber



42LCBL 42 Lexan Blue



42LCGN 42 Lexan Green



42LCOP 42 Lexan Opal



42LCRD 42 Lexan Red



42LPR 42 Lexan Prismatic

Ball Globes

These globes are used inside the RLM Series. The ball globes are not compatible with guards.

AG10

10" Diameter. Opal Glass

GG6

6" Diameter. Opal Glass Globe



PG10


10" Diameter. Opal Poly Globe

AT STYLE REFLECTOR

Decorative Reflectors

E MOUNTING

Cord Mounting			
643-10FT Cord Canopy, 10ft.	643-20FT Cord Canopy, 20ft.	643HD-10FT Heavy Duty Cord Canopy, 10ft.	643HD-20FT Heavy Duty Cord Canopy, 20ft.
503-10FT Cord Canopy with 3 Aircraft Cables, 10ft	503-20FT Cord Canopy with 3 Aircraft Cables, 20ft	<p>649-10FT-WH Basic Economical White Cord & Canopy Setup, 10FT</p> <p>Basic Economical Cord, Socket & Canopy assembly for RLMs in indoor applications.</p> <p>Cord: 10ft White 3C, 120V</p> <p>Canopy: Mounts to 4in Octagon jBox</p> 	<p>649-10FT-BK Basic Economical Black Cord & Canopy Setup, 10FT</p> <p>Basic Economical Cord, Socket & Canopy assembly for RLMs in indoor applications.</p> <p>Cord: 10ft Black 3C, 120V</p> <p>Canopy: Mounts to 4in Octagon jBox</p> 

<p>BDC - Small Ceiling Driver Enclosure</p> <p><i>Small Driver Enclosure Canopy for LED modules with small form drivers. Will work with a max of 2 PSB Drivers or 1 Lutron driver. 30W Max per driver. Accepts cord, 1/2-NPT stem, 3/4-NPT stem, single aircraft cable, or three aircraft cables. Dimensions: OD 5.5in x 2in</i></p>	
--	---

BDC6C-10FT BDC Style Driver Enclosure with 10ft Cord	BDC6C-20FT BDC Style Driver Enclosure with 20ft Cord	BDC6S-75 BDC Style Driver Enclosure for 3/4-NPT Stem	BDC6S-50 BDC Style Driver Enclosure for 1/2-NPT Stem
BDC6C1A-10FT BDC Style Driver Enclosure with 1 Aircraft Cable & 10ft Cord.	BDC6C1A-20FT BDC Style Driver Enclosure with 1 Aircraft Cable & 20ft Cord.	BDC6C3A-10FT BDC Style Driver Enclosure with 3 Aircraft Cable & 10ft Cord.	BDC6C3A-20FT BDC Style Driver Enclosure with 3 Aircraft Cable & 20ft Cord.